



- NOTES**
- UNITS MUST BE ATTACHED TO IN-PLANT COMPRESSED AIR SUPPLY FOR CLEANING MECHANISM TO FUNCTION (80 MAX psig CLEAN DRY AIR)
  - WELDED STEEL CONSTRUCTION OF 12 Gd. MILD STEEL.
  - FINISH: INDUSTRIAL GRADE CRIMSON RED INSIDE & OUT.
  - DUST TRAY CAPACITY: 1.75 CUBIC FT.
  - INLET COLLAR SIZES 6 IN. 8 IN.

**SPECIFICATIONS**  
 TOTAL VALVES, 1  
 TOTAL CARTRIDGES, 2  
 COMPRESSED AIR 1.0 SCF @80psi per sec.

|                   |        |                                       |     |            |          |
|-------------------|--------|---------------------------------------|-----|------------|----------|
| FILE              |        | TOLERANCES UNLESS OTHERWISE SPECIFIED |     |            |          |
| RP2 SPECIFICATION |        | 3 DEC. PLACE +/- .00                  |     |            |          |
|                   |        | 4 DEC. PLACE +/- .000                 |     |            |          |
|                   |        | ANGLES 1/2°                           |     |            |          |
|                   |        | UNLESS NOTED OTHERWISE                |     |            |          |
|                   |        | NTS                                   |     |            |          |
| DWG. BY           | DATE   | CHKD. BY                              | DRW | SH. 1 OF 1 | REV. NO. |
| MC                | 2-2-98 | JJ                                    | 11  |            | 1        |
|                   |        |                                       |     | EVEN NO.   | 1582     |