



BREATHE EASY...Solutions for Clean, Safe Air

MC2500

Specifications and Technical Data

TYPICAL APPLICATIONS:

SOURCE CAPTURE OF:

- WELD SMOKE AND FUMES
- CUTTING SMOKE AND FUMES
- GRINDING DUST
- SANDING DUST
- PARTICULATE GENERATED IN FILLING / MIXING PROCESS
- OTHER DRY POWDERS OR DUSTS
- ODOR CONTROL



STANDARD FEATURES:


- REVOLUTIONARY ROTO-PULSE® FILTER CLEANING SYSTEM
- EXTERNALLY SUPPORTED ARMS FOR EASY ADJUSTMENT
- MODULAR DESIGN—ONE OR TWO FILTER MODULES, UP TO FOUR ARMS
- UP TO 1,200 CFM PER 8" ARM
- QUIET OPERATION
- TEFC MOTOR
- FIRE RETARDANT CARTRIDGE FILTERS

OPTIONS:

- SILENCER
- OPTIONAL HEPA AND / OR CARBON MODULE AFTERFILTER
- VARIETY OF CARTRIDGE FILTER OPTIONS
- SINGLE OR DUAL FILTER MODULES
- SINGLE 8" DIA. ARM OR DUAL 6" DIA. ARMS PER FILTER MODULE

HOW IT WORKS:


Roto-Pulse provides for a much better cleaning of the cartridge filters. The air is pulsed into a specially designed aluminum, rotating tube, designed with pre-drilled holes. As the air enters this tube, the force of the pulse causes the tube to rotate inside the cartridge. While rotating, air exits the pre-drilled holes, effectively cleaning the entire length of the cartridge filter, resulting in a more efficient cleaning cycle and extended filter life.



L2241-MC2500-09/21



MC2500



MC2500 SPECIFICATIONS:

<p>OVERALL DIMENSIONS: ONE FILTER MODULE: 20" H X 36" W X 68" L TWO FILTER MODULES: 20" H X 36" W X 104" L</p> <p>WEIGHT: *500LBS ACTUAL WEIGHT (SINGLE FILTER MODULE) *720 LBS ACTUAL WEIGHT (DUAL FILTER MODULE) *WEIGHT VARIES DEPENDING UPON OPTIONS SELECTED CONSULT FACTORY FOR ARM WEIGHTS</p> <p>CABINET: HEAVY DUTY 16 GA. WELDED GALVANEAL STEEL W/EXTERIOR SURFACES GROUND SMOOTH</p> <p>FINISH: INDUSTRIAL GRADE TEXTURED BAKED CRIMSON RED ENAMEL PAINT—INSIDE AND OUT</p> <p>FILTRATION OPTIONS: TWO EA HIGH EFFICIENCY, FIRE-RETARDANT CARTRIDGE FILTERS PER FILTER MODULE FOR UP TO 696 SF MEDIA. FILTER OPTIONS INCLUDE: 80/20 POLY/CELLULOSE BLEND 100% SPUNBOND TREATED SPUNBOND NANO-FIBER</p> <p>CARTRIDGE CLEANING SYSTEM: ROTO-PULSE® UNIQUE ROTATING TUBE WITH PRE-DRILLED HOLES. AS AIR IS PULSED INTO THE TUBE, IT ROTATES AND AIR EXITS THE PRE-DRILLED HOLES, PROVIDING A HIGLY EFFICIENT AND TOTAL CLEANING OF THE CARTRIDGE FILTER.</p> <p>FILTER CHANGE INDICATOR: MAGNEHELIC GAUGE</p> <p>FILTER ACCESS: END LOAD THROUGH HINGED DOOR FOR EASY ACCESS</p> <p>Specifications subject to change without notification</p>	<p>ARM OPTIONS: 6" AND 8" DIAMATER, 7', 9' OR 12' LENGTHS, 8" DIA. SINGLE ARM PER MODULE OR DUAL 6" DIA . ARMS PER MODULE HALOGEN LIGHT IN HOOD STANDARD. FULL 360 DEGREE ROTATION AT BASE.</p> <p>NOISE LEVEL: 75 dBA @ 6" FROM EXHAUST</p> <p>INLET / EXHAUST: INLET AT HOOD OF SOURCE CAPTURE ARM / EXHAUST OUT FRONT OF UNIT</p> <p>MOTOR OPTIONS: SINGLE SPEED, 5 HP, 208-230/460 V, 60 HZ, 3 PAHSE, TEFC MOTOR DUAL SHAFT MOTOR INCLUDED WITH DUAL FILTER MODULE SYSTEM</p> <p>BLOWER: 12.6" DIA. BACKWARD INCLINED IMPELLER WHEEL (S)</p> <p>ELECTRICAL 208-230/460 V, 3-PHASE, 60 HZ ELECTRICAL UNIT ON/OFF SWITCHES & LIGHT ON/OFF SWITCHES OPERATE AT 12/24 VAC FOR OPERATOR SAFETY AND ARE LOCATED AT ARM HOOD MOTOR STARTER AND OVERLOAD RELAY EQUIPPED STANDARD</p> <p>MAX CURRENT 208/230V: 15.0 FLA 460V: 7.5 FLA</p> <p>AIR VOLUME: 650 CFM PER 6" DIA ARM 1200 CFM PER 8" DIA ARM NOMINALLY RATED—CONSULT BLOWER CURVES FOR DETAILS</p> <p>CONTROLS: ALL CONTROLS HOOD MOUNTED FOR EASE OF OPERATION REMOTE MOUNT SWITCHES & WIRE EXTENSIONS AVAILABLE—OPTIONAL</p>
---	--